

Technical Specifications:

Material	Material Specification
Weight	Weight Specification
Dimensions	Dimensions Specification
Temperature Range	1. 5°C. 2. 15°C. 3. 20°C. 4. 25°C. 5. 30°C. 6. 35°C. 7. 40°C. 8. 45°C. 9. 50°C. 10. 55°C. 11. 60°C. 12. 65°C. 13. 70°C. 14. 75°C. 15. 80°C. 16. 85°C. 17. 90°C. 18. 95°C. 19. 100°C. 20. 105°C. 21. 110°C. 22. 115°C. 23. 120°C. 24. 125°C. 25. 130°C. 26. 135°C. 27. 140°C. 28. 145°C. 29. 150°C. 30. 155°C. 31. 160°C. 32. 165°C. 33. 170°C. 34. 175°C. 35. 180°C. 36. 185°C. 37. 190°C. 38. 195°C. 39. 200°C. 40. 205°C. 41. 210°C. 42. 215°C. 43. 220°C. 44. 225°C. 45. 230°C. 46. 235°C. 47. 240°C. 48. 245°C. 49. 250°C. 50. 255°C. 51. 260°C. 52. 265°C. 53. 270°C. 54. 275°C. 55. 280°C. 56. 285°C. 57. 290°C. 58. 295°C. 59. 300°C. 60. 305°C. 61. 310°C. 62. 315°C. 63. 320°C. 64. 325°C. 65. 330°C. 66. 335°C. 67. 340°C. 68. 345°C. 69. 350°C. 70. 355°C. 71. 360°C. 72. 365°C. 73. 370°C. 74. 375°C. 75. 380°C. 76. 385°C. 77. 390°C. 78. 395°C. 79. 400°C. 80. 405°C. 81. 410°C. 82. 415°C. 83. 420°C. 84. 425°C. 85. 430°C. 86. 435°C. 87. 440°C. 88. 445°C. 89. 450°C. 90. 455°C. 91. 460°C. 92. 465°C. 93. 470°C. 94. 475°C. 95. 480°C. 96. 485°C. 97. 490°C. 98. 495°C. 99. 500°C.
Color	~ 5000000 10000000 Color Specification
Surface Finish	Surface Finish Specification
Texture	Texture Specification
Markings	1.Unique 2.Lowest 3.Highest 4.Soonest
Testing Methods	1. 2. Any 3. 4. 5.

Additional Information:

1. The 580°Celsius is poisonless.
2. the specification is the most accurate.
3. Carving is the most accurate.
4. our SGS FDA LFGB BV

Notes:



□□□□ □□ □□□□□□:

□□ □□ □□□□

□□□□□□ □□□□□ □□□□□ □□□ □□□□



□□□□□ □□□□:



□□□□ □□□:



□□□□□□ □□□□□□